



TF-AVS

## Ironing tables without boiler



### FEATURES

TF-A / TF-AS / TF-AVS

**Models equipped with built-in vacuum unit, without electric boiler (to be connected to central steam supply):**

- Vacuum ironing table + iron, with electrically heated board and suction.
- Adjustable temperature of board by means of a thermostat.
- Built-in single phase suction unit.
- Board dimensions: 1.200 x 400 x 250 mm
- Works by means of pedal.
- Automatic water feeding and pressure control
- Water pump
- To be connected to external steam supply.
- Adjustable height of board for model TF-AS from 750 to 950 mm

**TF-A:** heated and vacuum table

**TF-AS:** heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

**TF-AVS:** heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



### OPTIONS

- Vacuum sleeve arm for TF-AVS/TFC-AVS
- Steam gun for TF-AVS/TFC-AVS
- Sliding trolley with light for TF-AVS/TFC-AVS

CAPACITY	UNIT.	TF-AVS
Boiler	-	NO
Boiler capacity	l	-
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	N/A
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT.
Steam gun	-	OPT.
Sliding trolley with balancer and lighting	-	OPT.
Second steam iron assembly	-	N/A
POWER		
Vacuum Motor	kW	0,45
Pump Motor	kW	-
Iron Heater	kW	0,83
Board heater	kW	-
Boiler Heater	kW	-
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	4-5
Steam Consumption	kg/h	10-15
Ø Air inlet	BSP	1/4"
Air pressure	BAR	4-8
Air Consumption	l/min	5
OVERALL DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.680 / 1.880
Net depth / Gross depth	mm	580 / 680
Net height / Gross height	mm	920 / 1.270
Net weight / Gross weight	kg/h	141 / 165
Volume	m <sup>3</sup>	0,90 / 1,62
OTHER		
Voltage 50-60Hz	Hz	230V   50
Sound level	dB	75

