



# SPE800-2600

## SPE compact ironers

### FEATURES

SPE models are ironers that dries, irons and folds with a lengthwise and crosswise folder. They can be equipped with a stacker as option: 2 models available.

- Roll dimensions: working width 2m60 and 3m30, ø 600, 800 or 1000 mm
- 1 or 2 working lanes: one for bedsheets and two lanes for table cloth and small pieces.
- Length fold (1 or 2 folds) and crossfold (up to 3 folds)
- Folding by photocells and compressed air.
- 2 types of stacker as option, with possibility to program the number of stacked items. The stacker can be located on either side to the machine.
- Frequency inverter.
- Feeding and ironing by Nomex quality belts.
- Panels in white painted steel.
- Polished steel roll with fingers guard.
- Touch screen control: programs can be created, with temperature and speed control:
  - between 3 and 10 m/min (ø 600 mm),
  - between 3 and 13 m/min (ø 800 mm),
  - between 4 and 18 m/min (ø 1000 mm)
- Big output capacity: depending on the residual moisture of the linen straight away from a high spin washer:
  - up to 140 kg/h (ø 600 mm)
  - up to 220 kg/h (ø 800 mm)
  - up to 290 kg/h (ø 1000 mm)
- Electric, gas or steam heating
- Powerful exhaust system
- Compressed air connexion required: pressure 6,5 bar




### OPTIONS

- Side stacker (up to 10 to 15 tablecloth and 10 bedsheets)
- Roll-off compact stacker 1 lane (up to 5 tablecloth)
- Vacuum belts to help linen feeding
- Automatic 1 lane clamp feeder (without vacuum feeding belts)
- By pass for rear exit
- Rear exit with table + by pass
- 2 lanes rear collector + by pass
- 4 lanes rear collector + by pass
- Double air pressure for thick linen
- Linen rejection system (dirty or torn)
- Remote service
- Other tension than 400V III+N 50Hz
- Maintenance kit
- Maritime packing pour COMPACT SPE
- Maritime packing for side stacker
- Maritime packing fro ROLL OFF
- Maritime packing for 2 lanes collector
- Maritime packing for 4 lanes collector



GENERAL DATA	UNIT.	SPE800-2600
Theoretical production* elec/steam/atm. Gas heating	Kg/h	170
Theoretical production* radiant gas burner	Kg/h	195
Ø Roll	mm	800
Working width	mm	2.600
Height floor-feeding	mm	1.050
Working speed	mt/min	3-13
Control type	-	Digital
Nº of programs	Nº	20
Side stacker	Nº	Opt.
FOLDING		
1 lane - lengthfold	Nº	1-2
1 lane - crossfold	Nº	1-2-3
2 lanes - lengthfold	Nº	1-2
2 lanes - crossfold	Nº	1-2
POWER		
Electric heating	kW	72
Max. electric power electric heating	kW	75,5
Gas heating (natural / LPG)	kW	86,95 / 91,70
Max. electric power gas heating	kW	3,5
Steam heating	kW	85
Max. electric power steam heating	kW	3,5
CONNECTIONS		
Ø Gas inlet	BSP	1"
Ø Steam inlet (12 bar max.)	BSP	1"
Ø Condensed (steam models)	BSP	1/2"
Ø Air inlet	BSP	12
DIMENSIONS / PACKAGING DIMENSIONS		
Net width / gross width	mm	3.740 / 3.900
Net depth / gross depth	mm	2.210 / 2.280
Net height / gross height	mm	2.300 / 2.230
Net weight / gross weight	Kg	3.350 / 3.750
Volume	m3	19,01 / 19,83
OTHERS		
No. Fume outlet	Nº	2
Ø Fume outlet	mm	160
Extraction rate	m3/h	2 x 1.000
Compressed air consumption (6,5 bar)	mm	19.000
Sound Level	dB	70

\*50% residual moisture, 140gr / m2 of cotton,100% roll use

Compact stacker  
(roll-off)



Standard side  
stacker



- A. Compressed air inlet
- C. Condensed discharge (steam model)
- E. Electrical connection
- F. Fumes extraction
- G. Gas inlet
- V. Steam inlet

Compact stacker (roll-off)

Standard stacker

	L	P		L	P
SPE800-2600	4.425	2.385	SPE600-2600	5.105	2.476
SPE800-3300	5.125	2.385	SPE600-3300	5.805	2.476

