

## FEATURES

### DES-F

#### **Cold spotting table with built-in suction unit and stainless steel vacuum swinging arm.**

- Featuring two cold spotting spray guns with independent circuits, two receptacles for liquids, hose support and swinging arm with suction and spotting shape out of stainless steel AISI 304.
- Board out of stainless steel AISI 304.
- Board dimensions: 800 x 260 x 175 mm.
- Electric connection: 230V I+N / 50-60 Hz.
- It needs compressed air : consumption 150 NI/min, air working pressure 6 bar.

### DES-F GC

- Model with built-in air compressor
- Electric connection 230/400V III 50Hz.

### MINI-DES

#### **Compact cold spotting table with built-in suction unit**

- Equipped with two cold spotting guns with independent circuit and two tanks for solvents.
- One working pedal.
- Stainless steel AISI 304 board (400 x 200 x 35 mm).
- Electric connection: 230V I+N / 50-60 Hz.
- It needs compressed air: consumption 30 NI/min, air working pressure 6-8 bar



## OPTIONS

- Steam gun for DES-F

GENERAL DETAILS	UNIT.	DES-F
Board dimensions	mm	800 x 260 x 175
Boiler	-	NO
Compressor	-	OPT
Steam gun	-	OPT
<b>POWER</b>		
Vacuum motor	HP	0,6
Compressor motor	kW	2
<b>CONNECTIONS</b>		
Ø Steam inlet	BSP	3/8"
Ø Condensate outlet	BSP	3/8"
Steam supply pressure	bar	4-6
Working steam pressure	bar	5
Steam consumption	kg/h	3-5
Ø Air inlet	BSP	1/4"
Ø Air outlet	mm	90
Air supply pressure	bar	5-8
Working air pressure	Kg/h	6
Air Consumption	NI/min	150
<b>DIMENSIONS / PACKING DIMENSIONS</b>		
Net width / Gross width	mm	1.270 / 1.300
Net depth / Gross depth	mm	600 / 650
Alto neto / Alto bruto (folded antenna)	mm	1.900 / 1.160
Net weight / Gross weight	Kg	44 / 53
Volume	m <sup>3</sup>	1,45 / 0,98
<b>OTHERS</b>		
Voltage	V	230V 1~ 50-60
Sound level	dB	<70

