

FEATURES

DES-F

Cold spotting table with built-in suction unit and stainless steel vacuum swinging arm.

- Featuring two cold spotting spray guns with independent circuits, two receptacles for liquids, hose support and swinging arm with suction and spotting shape out of stainless steel AISI 304.
- Board out of stainless steel AISI 304.
- Board dimensions: 800 x 260 x 175 mm.
- Electric connection: 230V I+N / 50-60 Hz.
- It needs compressed air : consumption 150 NI/min, air working pressure 6 bar.

DES-F GC

- Model with built-in air compressor
- Electric connection 230/400V III 50Hz.

MINI-DES

Compact cold spotting table with built-in suction unit

- Equipped with two cold spotting guns with independent circuit and two tanks for solvents.
- One working pedal.
- Stainless steel AISI 304 board (400 x 200 x 35 mm).
- Electric connection: 230V I+N / 50-60 Hz.
- It needs compressed air: consumption 30 NI/min, air working pressure 6-8 bar



OPTIONS

- Steam gun for DES-F

GENERAL DETAILS	UNIT.	DES-F GC
Board dimensions	mm	800 x 260 x 175
Boiler	-	NO
Compressor	-	SÍ
Steam gun	-	OPT
POWER		
Vacuum motor	HP	0,6
Compressor motor	kW	2
CONNECTIONS		
Ø Steam inlet	BSP	3/8"
Ø Condensate outlet	BSP	3/8"
Steam supply pressure	bar	4-6
Working steam pressure	bar	5
Steam consumption	kg/h	3-5
Ø Air inlet	BSP	1/4"
Ø Air outlet	mm	90
Air supply pressure	bar	5-8
Working air pressure	Kg/h	6
Air Consumption	NI/min	150
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.270 / 1.300
Net depth / Gross depth	mm	600 / 650
Alto neto / Alto bruto (folded antenna)	mm	1.900 / 1.160
Net weight / Gross weight	Kg	78 / 118
Volume	m ³	1,45 / 0,98
OTHERS		
Voltage	V	230/400 V 3~ 50-60 Hz
Sound level	dB	<70

