



EASY TOUCH 2

7" touch screen, user-friendly and fully programmable
Connection USB. Free software online for programming,
telemetry, data analysis...
Videos display (ads, instructions...)
37 available languages
8 dosing signals as standard



G FACTOR

High G factor: reduced residual moisture, reduced drying time,
energy savings



EFFICIENCY

Optimized consumption: automatic or manual adjustment of
water levels and detergents according to the load
Water Saving system: 3 configurable levels of savings
Ready for water recovery tanks AQUABAC



VERSATILITY

ELECTRIC <> HOT WATER
MAKE TO ORDER: possibility to customize
WET CLEANING as standard



CONNECTIVITY

Communication Danube Online - IoT as standard
Remote technical service
Management of laundry
Multi-payment system



ERGONOMICS

Big aluminium door
Easy door lock system



MAINTENANCE

Hinged panel: easy access to parts
Technical menu: statistics, errors...



OTHERS

Free standing: no anchoring to the floor
Stainless steel vat and drum, skinplate outer casing
3 water inlets
Detergents box with compartments
Imbalance controlled by frequency inverter
CE standards and KIWA for REG4 standards



OPTIONS


- Dosing pumps kit DQ-2
- RT Ready for AQUABAC XL conn. 3/4" for washers WEN/WED-11/14/18/22/28
- Additional dosing pump DB-1
- DD Double drain kit WED-28
- NC Normally closed valve WED-28
- Kit WATERMARK Australia
- RC AQUA FLOW water recirculation kit WED-28 (not available with AQUABAC)
- LG Level feet kit WED-11 to 28
- WS weighing system WED-11 to 45C (additional 6 dosing signals included)
- XD 6 extra dosing signals card WED-11-45C
- SG Silicon gasket WED-18-22-28
- RD reverse door opening
- TR Protected board ET2 for WED-11-45C (standard on 60 to 120 kg models)
- Steam kit WED-28-35C-45C (to transform E or HW models to steam)
- Self plinth same height of machine stainless steel WED-28
- Self plinth same height of machine skinplate WED-28
- Ergonomic plinth stainless steel WED-28
- Ergonomic plinth skinplate WED-28
- 440V 3~ (No N) 50/60 Hz 28
- SSC Stainless steel outer casing WED-28
- 230V 3~ 50/60Hz 28E
- SSF Stainless steel front panel WED-28
- Supl 440V III 50/60 de 28 kg
- IoT licence - Danube Online
- Several payment systems for self-service
- UD Kit temporized door opening WED-WEN

DRUM		UNIT.	WED-28 ET2
Capacity 1/9		Kg	31
Capacity 1/10		Kg	28
Volume		l	280
Diameter		mm	770
Depth		mm	585
GENERAL DETAILS			
Washing speed / Spining speed		r.p.m.	45 / 1.024
G Factor		-	450
Maximum force transmitted		KN	5,59 ±1,75
Frequency-dynamic force		Hz	15
Noise level		dB	< 70
Coin laundry version		-	YES
Double drain		-	OPT.
Weighing system		-	OPT.
Tilting system		-	NO
DOOR			
Height door bottom		mm	560
Diameter		mm	460
POWER			
Motor		kW	4
Electric heating power		kW	18
Total electric power (electric model)		kW	19,2
Total electric power (hw, steam model)		barG	4
CONNECTIONS		E	HW/S
Tension 110V - I + N + T		Nº x mm ² / A	-
Tension 230V - I + N + T		Nº x mm ² / A	-
Tension 230V - III + T		Nº x mm ² / A	3x16+T - 63A
Tension 400V - III + N + T		Nº x mm ² / A	4x4+T - 32A
Steam inlet (Steam model)		inch	3/4"
Maximum steam consumtion (Steam model)		Kg/h	15
Water inlet		inch	3/4"
Water main pressuer		Kgs/cm ²	2-4
Maximum water consumption*		Lit/h	175,5*
Drain		mm/inch	3"
Drainage capacity		Lit/min	200
DIMENSIONS / PACKING DIMENSIONS			
Net Width/Gross width		mm	979 / 1.045
Net Depth/Gross depth		mm	1.080 / 1.210
Net Height / Gross height		mm	1.550 / 1.810
Net weight / Gross weight		kg	524,5 / 548,5
Volume		m ³	2,28

* Program number 20: WED-11 to WED-80C at 75% load /WED-100C and 120C at 100% load.

** 400V version / 230V version





	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ	
WED-28	mm	979	1 080	1 550	560	460	133	490	1 282	1 450	1 259	1 465	1 354	61	74	101	481	561	861	673	367	909	831	1 424	624	1 510	773	735

