

WEN-60C ET2

Low spin washers



EASY TOUCH 2

7" touch screen, user-friendly and fully programmable
Connection USB. Free software online for programming, telemetry, data analysis...
Videos display (ads, instructions...)
37 available languages
8 dosing signals as standard



G FACTOR

G factor 200/150 (WED-60C/80C)



EFFICIENCY

Optimized consumption: automatic or manual adjustment of water levels and detergents according to the load
Water Saving system: 3 configurable levels of savings



VERSATILITY

OPL <> SELF-SERVICE
ELECTRIC <> HOT WATER
MAKE TO ORDER: possibility to customize
WET CLEANING as standard



CONNECTIVITY

Communication Danube Online - IoT as standard
Remote technical service
Management of laundry
Multi-payment system



ERGONOMICS

Big aluminium door
Easy door lock system



MAINTENANCE

Hinged panel: easy access to parts
Same parts for all the models: electronic components, gear, inverter, contactors
Technical menu: statistics, errors...



OTHERS

Hard mounted washers to be anchored to the floor
Stainless steel vat and drum, skinplate outer casing
3 water inlets
Detergents box with compartments
Imbalance controlled by frequency inverter
CE standards and KIWA certificate for REG4 standards.



OPTIONS


- Dosing pumps kit DQ-2
- Additional dosing pump DB-1
- RT Ready for AQUABAC XL conn. 1" for washers WEN/WED-60C/80C
- Anchoring base WEN-60C
- DD Double drain kit WEN-60C-80C
- Kit WATERMARK Australia
- Water hose kit WED/WEN-60C/80C (one per water intake)
- XD 6 extra dosing signals card WEN-60C/80C
- RD reverse door opening
- TR Tropicalized model (ET2) 11-80
- Steam kit WEN-60C/80C (to transform E or HW models to steam)
- SSC Stainless steel outer casing WEN-60C
- SSF Stainless steel front panel WEN-60C
- 440V 3~ (No N) 50/60 Hz 60C
- 230V 3~ 50/60Hz 60C
- IoT licence - Danube Online
- Several payment systems for self-service
- UD Kit temporized door opening WED-WEN

DRUM	UNIT.	WEN-60C ET2	
Capacity 1/9	Kg	65	
Capacity 1/10	Kg	59	
Volume	l	600	
Diameter	mm	1.048	
Depth	mm	684	
GENERAL DETAILS			
Washing speed / Spining speed	r.p.m.	42,5 / 505	
G Factor	-	150	
Maximum force transmitted	KN	9,12 ±15	
Frequency-dynamic force	Hz	6,93	
Noise level	dB	< 70	
Coin laundry version	-	YES	
Double drain	-	OPT.	
Weighing system / Tilting door	-	NO	
SLUICE option	-	NO	
DOOR			
Height center door / Height door	mm	900 / 540	
Diameter	mm	560	
POWER			
Motor	kW	5,5	
Electric heating power	kW	36	
Total electric power (electric model)	kW	38	
Total electric power (hw, steam model)	barG	5,5	
CONNECTIONS		E	HW/S
Tension 110V - I + N + T	Nº x mm² / A	-	-
Tension 230V - I + N + T	Nº x mm² / A	-	-
Tension 230V - III + T	Nº x mm² / A	3x25+T - 100A	3x4+T - 32A
Tension 400V - III + N + T	Nº x mm² / A	4x16+T - 63A	4x1,5+T - 16A
Steam inlet (Steam model)	inch	3/4"	3/4"
Maximum steam consumption (Steam model)	Kg/h	21	
Water inlet	inch	1"	
Water main pressuer	Kgs/cm²	2-4	
Maximum water consumption	Lit/h	627,9*	
Drain	mm/inch	3"	
Drainage capacity	Lit/min	200	
DIMENSIONS / PACKING DIMENSIONS			
Net Width/Gross width	mm	1.225 / 1.335	
Net Depth/Gross depth	mm	1.315 / 1.440	
Net Height / Gross height	mm	1.640 / 1.860	
Net weight / Gross weight	kg	792 / 878	
Volume	m³	2,64 / 3,6	

* Program number 20: WEN-11 to WED-45C at 75% load / WEN-60C and 80C at 100% load.

** 400V version / 230V version





1. Soap dispenser
2. Emergency stop
3. USB port
4. Drain
5. Electric connection to liquid soap pumps
6. Electrical connection
7. Main switch
8. Auxiliar water inlet
9. Hot water inlet
10. Equipotential connection
11. Cold water inlet
12. Blur output / water overload
13. Liquid soap connection
14. Steam connection
15. Ethernet port

		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
WEN-60C	mm	1 225	1 315	1 640	540	560	140	984	1 368	1 536	1 306	1 551	1 318	61	74	101	651	731	1 110	869	270	1 163	1 080	1 470	992	1 595	644	972
WEN-80C	mm	1 225	1 492	1 640	540	560	140	984	1 368	1 536	1 306	1 551	1 318	61	74	101	651	731	1 110	869	270	1 163	1 080	1 470	992	1 595	644	750