



FEATURES

TPC-08 A / TPC-A / TPC-BA / TPC-VBA / TPC-A PLUS

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250) except TPC-08 A, board dimensions: 1100 x 380 x 270 mm
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models TPC-A PLUS and TPC-BA : from 750 to 950 mm

TPC-08 A / TPC-A / TPC-A PLUS : heated and vacuum table

TPC-BA : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

TPC-VBA : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for TPC-08 A

CAPACITY		UNIT.	TPC-08 A
Boiler		-	YES
Boiler capacity		l	4
Board dimensions		mm	1.100 x 380 x 270
Adjustable height of board		-	N/A
OPTIONS			
Swinging arm with heated sleeve shape		-	OPT.
Steam gun		-	N/A
Sliding trolley with balancer and lighting		-	N/A
Second steam iron assembly		-	N/A
POWER			
Vacuum Motor		kW	0,13
Pump Motor		kW	-
Iron Heater		kW	0,8
Board heater		kW	0,7
Boiler Heater		kW	1,45
Sleeve-arm heater (option)		kW	0,09
CONNECTIONS			
Ø Water inlet		BSP	-
Ø Boiler exhaust (with boiler)		BSP	-
Ø Steam inlet		BSP	-
Steam pressure		BAR	2,8
Steam Consumption		kg/h	-
Ø Air inlet		BSP	-
Air pressure		BAR	-
Air Consumption		Nl/min	-
OVERALL DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width		mm	1.380 / 1.300
Net depth / Gross depth		mm	380 / 540
Net height / Gross height		mm	930 / 1.160
Net weight / Gross weight		kg/h	43 / 57
Volume		m3	0,49 / 0,81
OTHER			
Voltage 50-60Hz		Hz	230V 50
Sound level		dB	70

