



MP-4 A-C

Ironing tables with boiler



FEATURES

MP-4 A-C / MP-A-C / MP-AS-C / MP-ASV-C / MP-AC PLUS

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250) except MP-4 A-C, board dimensions: 1100 x 380 x 270 mm
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models MP-AC PLUS and MP-AS-C : from 750 to 950 mm

MP-4 A-C / MP-A-C / MP-AC PLUS : heated and vacuum table

MP-AS-C : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

MP-ASV-C : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for MP-4 A-C

CAPACITY	UNIT.	MP-4 A-C
Boiler	-	YES
Boiler capacity	l	4
Board dimensions	mm	1.100 x 380 x 270
Adjustable height of board	-	N/A
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT.
Steam gun	-	N/A
Sliding trolley with balancer and lighting	-	N/A
Second steam iron assembly	-	N/A
POWER		
Vacuum Motor	kW	0,13
Pump Motor	kW	-
Iron Heater	kW	0,8
Board heater	kW	0,7
Boiler Heater	kW	1,45
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	-
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
OVERALL DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.380 / 1.300
Net depth / Gross depth	mm	380 / 540
Net height / Gross height	mm	930 / 1.160
Net weight / Gross weight	kg/h	43 / 57
Volume	m ³	0,49 / 0,81
OTHER		
Voltage 50-60Hz	Hz	230V 50
Sound level	dB	70

