



TCC

Steam generators



FEATURES

SB-2

- Electric steam boiler with steam iron.
- Small, thermically insulated, electric steam boiler.
- Die-cast aluminium boiler, capacity 1,8 liters, heater 1 kw.
- Manually operated water feeding (drinking water required for its functioning).
- Automatic pressure control by thermostat with fixed setting.
- Mobile trolley as option.

SB-5

- Stainless steel electric steam boiler with electric steam iron.
- Boiler capacity 5 lt, heater 1,45 kw.
- Water level indicator with warning light for empty boiler.
- Three safety devices fitted on the boiler: pressure switch, safety valve and safety thermostat.
- Manual water feed.
- Mobile trolley as option.

TCC

- Folding ironing table with electrically heated board and built in suction unit.
- Without steam iron, without built-in boiler
- Board dimensions: 1.100 x 380 x 240 mm

SB-24

ELECTRIC AND AUTOMATIC CENTRAL STEAM BOILER

- Automatic water feeding or ready to be connected to a condensate tank.
- Power available 12 or 22 kw, one set of heaters.
- Steam production: 16 or 29 kg/h.
- Boiler shell manufactured in accordance to the current PED regulations.
- Steam working pressure: 1 - 7 bar
- Boiler capacity 24,9 lt.
- Voltage 400V III+N / 230V III 50-60 Hz



GENERAL DETAILS		UNIT.	TCC
Boiler Capacity	l	-	-
Steam pressure	Bar	-	-
Working temperature	°C	-	-
Working humidity	-	-	-
Boiler Heater	kW	-	-
Iron Heater	kW	-	-
Resistance table	W	600	
Suction motor	W	100	
CONNECTIONS			
Boiler heaters	kW	-	-
Steam production	Kg/h	-	-
Pump motor power	HP	-	-
CONNECTIONS			
Water feeding inlet	Inch	-	-
Boiler exhaust	Inch	-	-
Steam inlet	Inch	-	-
Condensate return with valve	Inch	-	-
Autonomy	-	-	-
Operating pressure	BAR	-	-
DIMENSIONS			
Dimensions*	mm	1.380 x 380 x 930	
Net weight	kg	22	
Gross weight	kg	32	
Packing dimensions	mm	1.460 x 460 x 380	
Working dimensions	-	1.100 x 380 x 240	
OTHER			
Voltage	Hz	230V 50	
Sound level	dB	-	-

* Dimensions once assembled

