

# DD-14 BRONZE EM BRONZE dryers



## ELECTRONIC CONTROL

Easy-to-use electronic control with push buttons to control temperature and time



## FEATURES

Reversing drum action as standard  
Stainless steel drum as standard  
Frequency inverter as standard



## EFFICIENCY

**DOUBLE FLOW** - mixed axial-radial airflow  
Big fluff filter as drawer



## VERSATILITY

Make to order - customisation  
OPL > Multivending - Standard OPL model easily trasformable to coin laundry uses



## ERGONOMICS

Drawer as fluff filter, stainless steel mesh  
Big door diameters  
Opening sense of door adjustable on site



## MAINTENANCE

Hinged control panel: easy and ergonomic access  
Technical menu: statistics, data recovery for after-sales service, software updates, etc.  
Easy access to components



## OTHERS

Grey skinplate outer casing, stainless steel look  
**NEW:** transmission by gear motor on models DD-45 to 80  
**SOFT DRY** - new drum with stamped holes  
**COOL DOWN** - anti-wrinkle at the end of the cycle  
Electric, gas or steam heating  
CE approved




## OPTIONS

- DG Double doorglass DD-11-28
- NG Natural gas heated tumble dryer (LPG as standard)
- RD Opposite door opening 11-35
- BMS New display for EM programmer
- AF Back panel with air filter from 11 to 35
- F06 Fluff filter with grid 0,6mm (standard is 0,3mm)
- F12 Fluff filter with grid 1,2 mm (standard is 0,3 mm)
- SSC Stainless steel outer casing 14, 18
- SSF Stainless steel front panel 11, 14, 18
- BSS Stainless steel steam battery 11-14-18
- RP Reduced power (12kw instead of 18kw) for electric heated 14kg and 18kg models.
- WB Wooden packing 14,18
- 400V 3N 60 Hz DD--11-35
- 230V 3~ 50 Hz DD-11, 14, 18 E
- 230V 3~ 60 Hz DD-11,14, 18 E
- 230V 3~ 60 Hz DD-11,35 G/S
- 440/480V 3~ 60 Hz DD- 11,18
- Several payment systems for self-service

CAPACITY & DRUM		UNIT.	DD-14 BRONZE EM
Capacity 1/18		Kg	15
		lb	33,1
Capacity 1/20		Kg	13,5
		lb	29,8
Ø Drum		mm	750
		inch	29,53
Drum length		mm	610
		inch	24,02
Drum volume		l	270
		cu ft	9,53
Ø Door hole		mm	574
		inch	22,60
Door center height		mm	976
		inch	38,43
Height from floor to bottom of door		mm	618
		inch	24,33
ELECTRIC HEATING			
Evaporation capacity		L/h	13,5
		US gallon/h	3,6
Hourly output		Kg/h	26,9
		lb/h	59,3
Installed heating power		kW	18
Installed electrical power		kW	18,67
Drum motor power		kW	0,37
GAS HEATING			
Evaporation capacity		L/h	15,4
		US gallon/h	4,068
Hourly output		Kg/h	30,3
		lb/h	66,7
Installed gas heating power		kcal/h	17638
		Btu/h	70000
Installed gas heating power		kW	20,51
Installed electrical power		kW	0,67
Instant propane gas consumption (G31)		Kg/h	1,76
		lb/h	3,88
Instant natural gas consumption (G20)		m <sup>3</sup> /h	2,17
		cfm	1,28
Ø Gas inlet		BSPP ISO 228-1	1/2"
STEAM HEATING			
Installed steam heating power		kW	30
		Btu/h	102364
Installed electrical power		kW	0,67
Steam consumption (8 barG) - Standard		kg/h	53
Steam consumption (116 psiG)		lb/h	63,8
Steam pressure		barG	6 - 9
		psiG	87 - 130,5
Standard steam inlet - outlet		BSPT- ISO7.1	3/4"
Steam inlet - condensate outlet		NPT ANSI B1.20.1 Tapered	3/4"
Steam consumption (5 barG) - Low Pressure		kg/h	57
Steam consumption (72,5 psiG) - Low Pressure		lb/h	68,7
Steam pressure (low pressure)		barG	3 - 6
		psiG	43,5 - 89
Low pressure steam inlet - outlet		BSPT- ISO7.1	1"
VENTILATION			
Fan motor power		kW	0,25
Nominal air flow rate		m <sup>3</sup> /h	850
		cfm	500,29



Ø Fume exhaust	mm	200		
Ø Fume exhaust	inch	7,87		
<b>HEAT EMISSION</b>				
Maximum total heat emission	kW	1,8		
	Btu/h	6145,5		
Max. front heat emission	kW	1,26		
	Btu/h	4301,8		
<b>CONNECTIONS</b>				
Tension 230V - I + N + T	Nº x mm² / A	-	E	G / S
Tension 230V - III + T	Nº x mm² / A	4 x 16 / 63A		3 x 1,5 / 16A
Tension 400V - III + N + T	Nº x mm² / A	5 x 10 / 32A		3 x 1,5 / 16A
<b>NET DIMENSIONS / PACKING DIMENSIONS</b>				
Net / gross width	mm	785 / 865		
	inch	30,91 / 34,06		
Net / gross depth	mm	989 / 1.074		
	inch	38,94 / 42,28		
Net height / gross height (*without heating)	mm	1.694 / 1.840		
	inch	66,69 / 72,44		
Net / gross weight	Kg	180 / 190		
	lb	396,83 / 418,88		
<b>OTHERS</b>				
Sound level	dB	64		



- 01 POWER SUPPLY
- 02 FUMES OUTPUT Ø200
- 03 GAS INLET 1/2"
- 04 STEAM INLET 3/4"
- 05 CONDENSATE OUTLET 3/4"
- 06 ETHERNET CONNECTION (only available CONTROL ET2 models)

	A	B	C	D	D1	E	E1	F	G	H	I	J	K	L	M	N	O	P
DD-11	1694*	1447	689	1354	1422	68	68	785	855	735	380	870	575	1226	133	180	35	805
DD-14	1694*	1447	689	1354	1422	68	68	785	989	735	380	870	575	1226	133	180	35	805

\* Measurement with legs mounted (30mm)

