# TOPPER-C
# TOPPER

## FEATURES

### TOPPER / TOPPER-C

TWO AVAILABLE MODELS:

- **TOPPER** : to be connected to central steam supply
- **TOPPER-C :** with built-in boiler

With air-operated waistband and leg stretching device, for central steam and compressed air supplies
TOPPER model can be installed with steam genetor SB-24 - 12 kw
Side waistband stretching device
Height adjustable leg stretching carriage and leg clamps made of stainless steel
Built-in three phases fan. Air heating device
Electronic card for the setting of 9 ironing cycles in total
Ironing cycle controlling: steaming time, steam/air time, drying time
Three pressure regulators (for leg clamps, waistband stretcher and leg stretching carriage)
Switch for the exclusion of the leg stretching carriage
Manual size indicator
Mechanical airflow regulator
It needs compressed air, 5 bar - 40 Nl/min
Tension 230/400V III 50/60 Hz

| GENERAL DETAILS | UNIT. | TOPPER-C |
|---|---|---|
| Boiler | - | YES |
| Boiler capacity | L | 5 |
| Group of iron | - | - |
| Steam gun | - | - |
| **POWER** | | |
| Pump motor | HP | - |
| Boiler heater | kW | 6 |
| Fan motor | kW | 1-1,5 |
| **CONNECTIONS** | | |
| Ø Water inlet | BSP | - |
| Ø Boiler exhaust (mod. with boiler) | BSP | - |
| Ø Steam inlet | BSP | - |
| Ø Condensate outlet | BSP | - |
| Steam pressure | bar | 5 |
| Steam consumption | Kg/h | - |
| Ø Air inlet | BSP | 1/4" |
| Ø Air outlet | mm | - |
| Air pressure | bar | 5 |
| Air Consumption | Nl/min | 40 |
| **DIMENSIONS / PACKING DIMENSIONS** | | |
| Net width / Gross width | mm | 1.115 / 1.210 |
| Net depth / Gross depth | mm | 630 / 780 |
| Net height / Gross height | mm | 1.950 / 2.100 |
| Net weight / Gross weight | kg | 165 / 225 |
| Volume | $m^3$ | 1,37 / 1,98 |
| **OTHERS** | | |
| Voltage | V | 230/400V 3~ 50-60 |
| Sound level | dB | 70 |