

TOPPER-C
TOPPER

FEATURES

TOPPER / TOPPER-C

TWO AVAILABLE MODELS:

- **TOPPER** : to be connected to central steam supply
- **TOPPER-C :** with built-in boiler

With air-operated waistband and leg stretching device, for central steam and compressed air supplies
TOPPER model can be installed with steam genetor SB-24 - 12 kw
Side waistband stretching device
Height adjustable leg stretching carriage and leg clamps made of stainless steel
Built-in three phases fan. Air heating device
Electronic card for the setting of 9 ironing cycles in total
Ironing cycle controlling: steaming time, steam/air time, drying time
Three pressure regulators (for leg clamps, waistband stretcher and leg stretching carriage)
Switch for the exclusion of the leg stretching carriage
Manual size indicator
Mechanical airflow regulator
It needs compressed air, 5 bar - 40 Nl/min
Tension 230/400V III 50/60 Hz



GENERAL DETAILS	UNIT.	TOPPER-C
Boiler	-	YES
Boiler capacity	L	5
Group of iron	-	-
Steam gun	-	-
POWER		
Pump motor	HP	-
Boiler heater	kW	6
Fan motor	kW	1-1,5
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (mod. with boiler)	BSP	-
Ø Steam inlet	BSP	-
Ø Condensate outlet	BSP	-
Steam pressure	bar	5
Steam consumption	Kg/h	-
Ø Air inlet	BSP	1/4"
Ø Air outlet	mm	-
Air pressure	bar	5
Air Consumption	Nl/min	40
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.115 / 1.210
Net depth / Gross depth	mm	630 / 780
Net height / Gross height	mm	1.950 / 2.100
Net weight / Gross weight	kg	165 / 225
Volume	m^3	1,37 / 1,98
OTHERS		
Voltage	V	230/400V 3~ 50-60
Sound level	dB	70