

FEATURES

MP-4 A-C / MP-A-C / MP-AS-C / MP-ASV-C / MP-AC PLUS

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250) except MP-4 A-C, board dimensions: 1100 x 380 x 270 mm
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models MP-AC PLUS and MP-AS-C : from 750 to 950 mm

MP-4 A-C / MP-A-C / MP-AC PLUS : heated and vacuum table

MP-AS-C : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

MP-ASV-C : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for MP-A/MP-A-C/MP-AS/MP-AS-C
- Steam gun for MP-A/MP-A-C/MP-AS/MP-AS-C
- Sliding trolley with light for MP-A/MP-A-C/MP-AS/MP-AS-C
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	MP-A-C
Boiler	-	YES
Boiler capacity	l	5
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	N/A
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT.
Steam gun	-	OPT.
Sliding trolley with balancer and lighting	-	OPT.
Second steam iron assembly	-	OPT.
POWER		
Vacuum Motor	kW	0,45
Pump Motor	kW	-
Iron Heater	kW	0,83
Board heater	kW	1
Boiler Heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	l/min	-
OVERALL DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.550 / 1.520
Net depth / Gross depth	mm	580 / 580
Net height / Gross height	mm	950 / 1.140
Net weight / Gross weight	kg/h	87 / 103
Volume	m ³	0,85 / 1,01
OTHER		
Voltage 50-60Hz	Hz	230/400 V III
Sound level	dB	68

