Ironing tables with boiler

FEATURES TFC-A / TFC-AR / TFC-AS / TFC-AVS

Models equipped with built-in vacuum unit and electric boiler :

• Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.

- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250).
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control

 \bullet Adjustable height of board for models TFC-AR and TFC-AS: from 750 to 950 mm

TFC-A / TFC-AR: heated and vaccum table

TFC-AS: heated, vaccuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

TFC-AVS: heated, vaccuum, up-steaming and blowing table • Built-in single-phase suction and blowing device, controlled by

double pedal

Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for TF-A/TFC-A/TFC-AR/TF-AS/TFC-AS
- Steam gun for TF-A/TFC-A/TFC-AR/TF-AS/TFC-AS
- Sliding trolley with light for TF-A/TFC-A/TFC-AR/TF-AS/TFC-AS
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	TFC-A
Boiler	-	YES
Boiler capacity	I	5
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	N/A
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT.
Steam gun	-	OPT.
Sliding trolley with balancer and lighting	-	OPT.
Second steam iron assembly	-	OPT.
POWER		
Vacuum Motor	kW	0,45
Pump Motor	kW	-
Iron Heater	kW	0,83
Board heater	kW	1
Boiler Heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	Nl/min	-
OVERALL DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.550 / 1.520
Net depth / Gross depth	mm	580 / 580
Net height / Gross height	mm	950 / 1.140
Net weight / Gross weight	kg/h	87 / 103
Volume	m3	0,85 / 1,01
OTHER		
Voltage 50-60Hz	Hz	230/400 V III
Sound level	dB	68

 \bigcirc