



TPC-BA

Ironing tables with boiler



FEATURES

TPC-A / TPC-BA / TPC-VBA / TPC-A PLUS

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250).
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models TPC-A PLUS and TPC-BA : from 750 to 950 mm

TPC-A / TPC-A PLUS : heated and vacuum table

TPC-BA : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

TPC-VBA : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for TP-A/TPC-A/TP-BA/TPC-BA
- Steam gun for TP-A/TPC-A/TP-BA/TPC-BA
- Sliding trolley with light for TP-A/TPC-A/TP-BA/TPC-BA
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	TPC-BA
Boiler	-	YES
Boiler capacity	l	5
Board dimensions	mm	1.200 x 400 x 270
Adjustable height of board	-	YES
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT.
Steam gun	-	OPT.
Sliding trolley with balancer and lighting	-	OPT.
Second steam iron assembly	-	OPT.
POWER		
Vacuum Motor	kW	0,45
Pump Motor	kW	-
Iron Heater	kW	0,83
Board heater	kW	1
Boiler Heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	l/min	-
OVERALL DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.500 / 1.520
Net depth / Gross depth	mm	600 / 580
Net height / Gross height	mm	1.800 / 1.120
Net weight / Gross weight	kg/h	100 / 116
Volume	m ³	1,62 / 0,99
OTHER		
Voltage 50-60Hz	Hz	230/400V III
Sound level	dB	70

