



FEATURES

TPC-08 A / TPC-A / TPC-BA / TPC-VBA / TPC-A PLUS

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250) except TPC-08 A, board dimensions: 1100 x 380 x 270 mm
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models TPC-A PLUS and TPC-BA : from 750 to 950 mm

TPC-08 A / TPC-A / TPC-A PLUS : heated and vacuum table

TPC-BA : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

TPC-VBA : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for TP-A/TPC-A/TP-BA/TPC-BA
- Steam gun for TP-A/TPC-A/TP-BA/TPC-BA
- Sliding trolley with light for TP-A/TPC-A/TP-BA/TPC-BA
- Second iron (models with electric boiler only)

CAPACITY		UNIT.	TPC-BA
Boiler		-	YES
Boiler capacity	l		5
Board dimensions	mm		1.200 x 400 x 270
Adjustable height of board	-		YES
OPTIONS			
Swinging arm with heated sleeve shape	-		OPT.
Steam gun	-		OPT.
Sliding trolley with balancer and lighting	-		OPT.
Second steam iron assembly	-		OPT.
POWER			
Vacuum Motor	kW		0,45
Pump Motor	kW		-
Iron Heater	kW		0,83
Board heater	kW		1
Boiler Heater	kW		3,9
Sleeve-arm heater (option)	kW		0,09
CONNECTIONS			
Ø Water inlet	BSP		3/8"
Ø Boiler exhaust (with boiler)	BSP		3/8"
Ø Steam inlet	BSP		-
Steam pressure	BAR		2,8
Steam Consumption	kg/h		-
Ø Air inlet	BSP		-
Air pressure	BAR		-
Air Consumption	Nl/min		-
OVERALL DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width	mm		1.500 / 1.520
Net depth / Gross depth	mm		600 / 580
Net height / Gross height	mm		1.800 / 1.120
Net weight / Gross weight	kg/h		100 / 116
Volume	m3		1,62 / 0,99
OTHER			
Voltage 50-60Hz	Hz		230/400V III
Sound level	dB		70

