



## S600-2600 S compact ironers



### FEATURES

S models are ironers that dry and iron only, without any folding devices

- Roll dimensions: working width 2m60 and 3m30, ø 600, 800 or 1000 mm.
- Frequency inverter.
- Feeding and ironing by Nomex quality belts.
- Panels in white painted steel.
- Polished steel roll with fingers guard.
- Touch screen control: programs can be created with temperature and speed control:
  - between 3 and 10 m/min (ø 600 mm)
  - between 3 and 13 m/min (ø 800 mm)
  - between 4 and 18 m/min (ø 1000 mm)
- Big output capacity: depending on the residual moisture of the linen, straight from a high spin washer extractor:
  - up to 140 kg/h (ø 600 mm)
  - up to 220 kg/h (ø 800 mm)
  - up to 290 kg/h (ø 1000 mm)
- Electric, gas or steam heating
- Powerful exhaust system
- Compressed air connexion required: pressure 6,5 bar





### OPTIONS

- Vacuum belts to help linen feeding
- Automatic 1 lane clamp feeder (without vacuum feeding belts)
- Rear exit + by pass
- Motorized rear exit - height 860 mm. (rear exit included)
- Small pieces back collector: 2 lanes for S
- Small pieces back collector: 4 lanes for S
- Different voltage from 400V III +N 50Hz
- Maritime packing for S

GENERAL DATA		UNIT.	S600-2600
Theoretical production* elec/steam/atm. Gas heating		Kg/h	125
Theoretical production* radiant gas burner		Kg/h	-
Ø Roll		mm	600
Working width		mm	2.600
Height floor-feeding		mm	1.050
Working speed		mt/min	3-10
Control type		-	Digital
Nº of programs		Nº	20
POWER			
Electric heating		kW	54
Max. electric power electric heating		kW	55,9
Gas heating (natural / LPG)		kW	63,30 / 67,40
Max. electric power gas heating		kW	1,9
Steam heating		kW	55
Max. electric power steam heating		kW	1,9
CONNECTIONS			
Ø Gas inlet		BSP	1"
Ø Steam inlet (12 bar max.)		BSP	1"
Ø Condensed (steam models)		BSP	1/2"
Ø Air inlet		BSP	12
DIMENSIONS / PACKAGING DIMENSIONS			
Net width / gross width		mm	3.670 / 3.830
Net depth / gross depth		mm	1.440 / 1.620
Net height / gross height		mm	2.030 / 1.960
Net weight / gross weight		Kg	1.800 / 2.050
Volume		m3	10,73 / 12,16
OTHERS			
No. Fume outlet		Nº	2
Ø Fume outlet		mm	120
Extraction rate		m3/h	2 x 1.000
Compressed air consumption (6,5 bar)		mm	5.000
Sound Level		dB	70

\*50% residual moisture, 140gr / m2 cotton,100% roll use



- A. Compressed air inlet
- B. Rear collector
- C. Condensed discharge (steam model)
- E. Electrical connection
- F. Fumes extraction
- G. Gas inlet
- V. Steam inlet

	H	I	T	S	A	C	E	F	G	V
S600-2600	1.800	3.242	186	152	Ø 12	1/2"	5 x 2,5	Ø 120	1"	1"
S600-3300	1.800	3.942	186	152	Ø 12	1/2"	5 x 2,5	Ø 120	1"	1"