

G-26 ET2

Ø 650 mm flatwork ironers



## EASY TOUCH 2

7" touch screen fully programmable  
37 available languages, 5 preset programs  
USB connection. Free software online for programming, telemetry, data analysis  
Reversing roll as standard




## EFFICIENCY

Good heat conduction thanks to the roll material and thickness:  
greater control of energy expenditure  
Automatic shutdown at 80°C (adjustable parameter)  
Fumes circulation circuit from the bottom reducing energy consumption

**Model with gas radiant burners: +25% productive**

**CARE IRON:** automatic regulation of ironing speed according to residual moisture as standard

**HPS:** high production system, ironing speed up to 15 m/min as standard



## ROBUSTNESS

Roll driving by speed inverter  
Nomex quality ironing belts: high temperatures resistant  
Panels in skinplate and stainless steel.  
Nickel plate roll as option: anticorrosive, more durable



## ERGONOMICS

Acoustic comfort : <65 dB  
Appropriate operating height: 1120 mm feeding belts  
Compact dimensions



## MAINTENANCE

Easy access to all components on both sides of the machine  
Complete technical menu: statistics, autotest, data recovery for technician and maintenance  
Remote communication: faster intervention



## OTHERS

Dries and irons flat linen from a high spin washer extractor in a single operation  
Front feeding and return  
Built-in cool down system  
Polished steel roll Ø 650 mm  
Working widths: 2000, 2600 and 3300 mm  
Electric, radiant gas or steam heating  
CE standard

## OPTIONS


- NI Nickel plate roll G-26 (except steam model)
- LPG Propan gas for radiant gas model
- NG Natural gas for radiant gas model
- LF Built-in lengthwise folder G-26 (front exit)
- RE Rear exit G-26 (only with folder)
- AB Antistatic ironing belts G-26 without folder
- FA Antistatic ironing belts + bar G-26 for folder
- PL Cross folder G-26
- WM Maritime Wood packaging for G-26
- 230V III 50-60Hz G-26 E
- 230V III 60Hz G-26 GR
- 440V III 50-60Hz G-26 E
- 120V I N 60Hz gas US G-26

GENERAL DETAILS	UNIT.	G-26 ET2	
Theoretical production Electric heating*	Kg/h	115	
	lb/h	254	
Theoretical production Gas atmo heating*	Kg/h	-	
	lb/h	N/A	
Theoretical production Radiant gas heating*	Kg/h	132	
	lb/l	291	
Theoretical production Steam heating*	Kg/h	-	
	lb/l	N/A	
Roll Ø	mm	650	
	inch	25,59	
Working width	mm	2.600	
	inch	102,36	
Height floor-feeding belts	mm	1.120	
	inch	44,09	
Working speed	m/min	0,5-15	
	ft/min	1.6-49	
Electronic control	-	YES	
No. Programs	-	5	
Lenght folder	-	OPT.	
Large surface contact with linen	-	310°	
POWER			
Electric mod.: heating power	Kw	54	
Electric mod: Total electric power	Kw	55,05	
Gas mod.: heating power	Kw	69	
Gas mod.: total electric power	Kw	1,05	
Steam mod.: heating power	Kw	76	
Steam mod.: total electric power	Kw	1,05	
Steam consumption	Kg/h	80	
Roll motor power	Kw	0,55	
Fan motor power	Kw	0,25 x 2	
CONNECTIONS		E	G/S
Tension 230V - I + N + T	Nº x mm² / A	N/A	3 x 2,5 / 10A
	nº x AWG/A	N/A	3 x 13 / 10A
Tension 230V - III + T	Nº x mm² / A	4 x 35 / 160A	4 x 2,5 / 10A
	nº x AWG/A	4 x 2 / 160A	4 x 13 / 10A
Tension 400V - III + N + T	Nº x mm² / A	5 x 25 / 100A	5 x 2,5 / 10A
	nº x AWG/A	5 x 3 / 100A	5 x 13 / 10A
Ø Gas inlet	BSP	1/2"	
Ø Steam inlet	BSP	3/4"	
Ø Condensed (Steam models)	BSP	1/2"	
OVERALL DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width	mm	3.445 / 3.745	
	inch	135,6 / 147,4	
Net depth / gross depth	mm	1.070 / 1.153	
	inch	42,1 / 45,4	
Net height / gross height	mm	1.420 / 1.672	
	inch	55,9 / 65,8	
Net weight / gross weight	kg	1.517 / 1.567	
	lbs	3.344 / 3.455	
Net volume / Gross volume	m³	5,23 / 7,22	
	f³	185 / -	
OTHERS			
No. Fume outlet	Nº	2	
Ø Fume outlet	mm	153	
	inch	6,0	
Air Flow	m³/h	1.200	
	cfm	706	



Sound level	dB	65
Evaporation power	l/h	59
	USgallon/h	15,7
Additional ELECTRIC POWER for folder option	-	0,56
Additional ELECTRIC POWER for folder + rear exit option	-	0,74

\* Theoretical production with 45% moisture



	A	B	C	D	E	F	G	H	I	J	K	L	M	N
G-20 ET2	1.420	2.845	36	Ø152	228	83	897	2.160	1.079	2.004	1.128	447	509	952
G-26 ET2	1.420	3.445	36	Ø152	228	83	897	2.760	1.079	2.604	1.128	447	509	952
G-33 ET2	1.420	4.145	36	Ø152	228	83	897	3.460	1.079	3.304	1.128	447	509	952

