



TPC-VBA

Ironing tables with boiler



FEATURES

TPC-08 A / TPC-A / TPC-BA / TPC-VBA / TPC-A PLUS

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250) except TPC-08 A, board dimensions: 1100 x 380 x 270 mm
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models TPC-A PLUS and TPC-BA : from 750 to 950 mm

TPC-08 A / TPC-A / TPC-A PLUS : heated and vacuum table

TPC-BA : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

TPC-VBA : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Vacuum sleeve arm for TP-VBA/TPC-VBA
- Steam gun for TP-VBA/TPC-VBA
- Sliding trolley with light for TP-VBA/TPC-VBA
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	TPC-VBA
Boiler	-	YES
Boiler capacity	l	7
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	N/A
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT.
Steam gun	-	OPT.
Sliding trolley with balancer and lighting	-	OPT.
Second steam iron assembly	-	OPT.
POWER		
Vacuum Motor	kW	0,45
Pump Motor	kW	0,75
Iron Heater	kW	0,83
Board heater	kW	-
Boiler Heater	kW	6-7,5
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	4,5
Steam Consumption	kg/h	-
Ø Air inlet	BSP	1/4"
Air pressure	BAR	4-8
Air Consumption	NI/min	5
OVERALL DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.680 / 1.880
Net depth / Gross depth	mm	580 / 680
Net height / Gross height	mm	920 / 1.270
Net weight / Gross weight	kg/h	141 / 165
Volume	m3	0,90 / 1,62
OTHER		
Voltage 50-60Hz	Hz	230/400V III
Sound level	dB	75

